







|               |   |   |   |   |                 |   |   |   |    |             |    |
|---------------|---|---|---|---|-----------------|---|---|---|----|-------------|----|
| 1             | 2 | 3 | 4 | 5 | 6               | 7 | 8 | 9 | 10 |             |    |
| POWER CIRCUIT |   |   |   |   | CONTROL CIRCUIT |   |   |   |    | ADDRESS NO. | B1 |



| SPECIFICATION | NO FUSE BREAKER |     | MAGNET CONTACT |       | TRANSFORMER | FUSE          |
|---------------|-----------------|-----|----------------|-------|-------------|---------------|
| SYMBOLS       | MCCB0           |     | M0             |       | TR10        | F11, F12, F21 |
| DESCRIPTION   | 220V            | 30A | GMC22          | DMC22 | 30VA        | 1A            |
|               | 380V            | 20A |                |       |             |               |
|               | 440V            | 20A |                |       |             |               |
|               | 460V            | 20A |                |       |             |               |
|               | 480V            | 15A |                |       |             |               |
| MAKER         | LS              |     | LS             | DONGA | LK          | —             |


|                                                                                                                  |         |                              |          |       |                                                                                       |       |
|------------------------------------------------------------------------------------------------------------------|---------|------------------------------|----------|-------|---------------------------------------------------------------------------------------|-------|
| TITLE                                                                                                            |         |                              |          |       | PROJECTION                                                                            |       |
| MAIN POWER & CONTROL CIRCUIT DIAGRAM                                                                             |         |                              |          |       |  |       |
| WORK                                                                                                             | NO      | WORK                         |          |       | NAME                                                                                  |       |
| 602                                                                                                              |         | SH5BM                        |          |       | SCALE                                                                                 | Q' TY |
|                                                                                                                  |         | 220V, 380V, 440V, 460V, 480V |          |       | 1/1                                                                                   | 1     |
|                                                                                                                  |         |                              |          |       |                                                                                       |       |
| DRAWN                                                                                                            | CHECKED | REVIEWED                     | APPROVED | MODEL | SH5BM                                                                                 |       |
| LEE.G.H                                                                                                          |         |                              |          | CODE  | NO                                                                                    |       |
| 2010.07.30                                                                                                       |         |                              |          |       |                                                                                       |       |
|  <b>L K HOIST CO., LTD.</b> |         |                              |          |       |                                                                                       |       |





| TITLE TRAVERSING MOTOR POWER & CONTROL CIRCUIT DIAGRAM |         |                              |          | PROJECTION |       |
|--------------------------------------------------------|---------|------------------------------|----------|------------|-------|
| WORK NO                                                |         | WORK NAME                    |          |            |       |
| 605                                                    |         | SHDBM                        |          | SCALE      | Q' TY |
|                                                        |         | 220V, 380V, 440V, 460V, 480V |          | 1/1        | 1     |
| DRAWN                                                  | CHECKED | REVIEWED                     | APPROVED | MODEL      | SHDBM |
| LEE.G.H                                                |         |                              |          | CODE NO    |       |
| 2010.07.30                                             |         |                              |          |            |       |
| L K HOIST CO., LTD.                                    |         |                              |          |            |       |

| SPECIFICATION |  | MAGNET CONTACT |       | Thermal Protector |  | TRAVERSING MOTOR |           |
|---------------|--|----------------|-------|-------------------|--|------------------|-----------|
| SYMBOLS       |  | M301, M302     |       | TP2               |  | TM               |           |
| DESCRIPTION   |  | GMC12          | DMC12 | 17AM032           |  | 0.75KW *4P       | 0.4KW *6P |
| MAKER         |  | LS             | DONGA | Texas Instruments |  | LK               |           |



| SPECIFICATION | MAGNET CONTACT   |       | Thermal Protector | SILICON RECTIFIER |        |        |        |        | TRAVERSING MOTOR   |
|---------------|------------------|-------|-------------------|-------------------|--------|--------|--------|--------|--------------------|
| SYMBOLS       | M301, M302, M303 |       | TP2               | DPM30             |        |        |        |        | TM                 |
| DESCRIPTION   | GMC12            | DMC12 | 17AM032           | AC220V            | AC380V | AC440V | AC460V | AC480V | 0.75/0.25KW *4/12P |
|               |                  |       |                   | DC99V             | DC171V | DC198V | DC207V | DC216V |                    |
| MAKER         | LS               | DONGA | Texas Instruments | LK                |        |        |        |        | LK                 |

TITLE TRAVERSING MOTOR POWER & CONTROL CIRCUIT DIAGRAM

WORK NO606

WORK NAMESHDBM

220V, 380V, 440V, 460V, 480V

PROJECTION

SCALE1/1

Q' TY1

DRAWNLEE.G.H

CHECKED

REVIEWED

APPROVED

MODEL

SHDBM

2010.07.30

CODE NO

L K HOIST CO., LTD.

|                                             |                             |                 |
|---------------------------------------------|-----------------------------|-----------------|
| SPECIFICATION FOR<br>ELECTRIC MOTORS        | INTERNAL IDENTIFICATION NO. | PAGE :<br>REV : |
| SCHEDULE OF TECHNICAL DATA                  |                             |                 |
| 1. SERVICE                                  | HOISTING                    |                 |
| 2. MANUFACTURE                              | LK HOIST CO. LTD            |                 |
| 3. MOTOR MODEL NO                           | 1.8/0.7 - 2/6 - 38          |                 |
| 4. RATED POWER                              | 1.8/0.7 KW × 2/6 P          |                 |
| 5. RATED VOLTAGE AND FREQUENCY              | 380 V      60HZ             |                 |
| 6. MOTOR TYPE                               | SQUIRREL CAGE ROTOR TYPE    |                 |
| 7. RATING                                   | 30 MIN                      |                 |
| 8. LOCATION                                 | IN-DOOR , OUTDOOR           |                 |
| 9. INSULATION CLASS                         | B                           |                 |
| 10. DESIGN TEMPERATURE RISE (BY RESISTANCE) | 80℃                         |                 |
| 11. FULL LOAD SPEED                         | 3440/1140 RPM               |                 |
| 12. FULL LOAD CURRENT                       | 6.8/2.7 A                   |                 |
| 13. STARTING CURRENT AT RATED VOLTAGE       | 35.3/14 A                   |                 |
| 14. MINIMUM STARTING VOLTAGE                | 342 V                       |                 |
| 15. EFFICIENCY AT 100% RATED LOAD           | 64/64 %                     |                 |
| 16. POWER FACTOR AT 100% RATED LOAD         | 64/64 %                     |                 |
| 17. STARTING TORQUE                         | 235 %                       |                 |
| 18. TYPE OF ENCLOSURE                       | 전폐형                         |                 |
| 19. TYPE OF BEARING                         | PL : 6205DD    OPL : 6008ZZ |                 |
| 20. MOUNTING                                | VERTICAL                    |                 |
| 21. MAXIMUM AMBIENT TEMPURE                 | 40℃                         |                 |
| 22. BEARING LUBRICATION                     | GREASE                      |                 |
| 23. STARTING METHOD                         | FULL VOLTAGE                |                 |

|                                             |                             |                 |
|---------------------------------------------|-----------------------------|-----------------|
| SPECIFICATION FOR<br>ELECTRIC MOTORS        | INTERNAL IDENTIFICATION NO. | PAGE :<br>REV : |
| SCHEDULE OF TECHNICAL DATA                  |                             |                 |
| 1. SERVICE                                  | TRAVERSING                  |                 |
| 2. MANUFACTURE                              | LK HOIST CO. LTD            |                 |
| 3. MOTOR MODEL NO                           | 0.75 - 4 - 38               |                 |
| 4. RATED POWER                              | 0.75 KW × 4 P               |                 |
| 5. RATED VOLTAGE AND FREQUENCY              | 380 V      60HZ             |                 |
| 6. MOTOR TYPE                               | SQUIRREL CAGE ROTOR TYPE    |                 |
| 7. RATING                                   | 15 MIN                      |                 |
| 8. LOCATION                                 | OUTDOOR                     |                 |
| 9. INSULATION CLASS                         | B                           |                 |
| 10. DESIGN TEMPERATURE RISE (BY RESISTANCE) | 100℃                        |                 |
| 11. FULL LOAD SPEED                         | 1670 RPM                    |                 |
| 12. FULL LOAD CURRENT                       | 2.77 A                      |                 |
| 13. STARTING CURRENT AT RATED VOLTAGE       | 15.2 A                      |                 |
| 14. MINIMUM STARTING VOLTAGE                | 342 V                       |                 |
| 15. EFFICIENCY AT 100% RATED LOAD           | 65 %                        |                 |
| 16. POWER FACTOR AT 100% RATED LOAD         | 63 %                        |                 |
| 17. STARTING TORQUE                         | 250 %                       |                 |
| 18. TYPE OF ENCLOSURE                       | 전폐형                         |                 |
| 19. TYPE OF BEARING                         | PL : 6008DD    OPL : 6207ZZ |                 |
| 20. MOUNTING                                | VERTICAL                    |                 |
| 21. MAXIMUM AMBIENT TEMPURE                 | 40℃                         |                 |
| 22. BEARING LUBRICATION                     | GREASE                      |                 |
| 23. STARTING METHOD                         | FULL VOLTAGE                |                 |

|                                             |                             |                 |
|---------------------------------------------|-----------------------------|-----------------|
| SPECIFICATION FOR<br>ELECTRIC MOTORS        | INTERNAL IDENTIFICATION NO. | PAGE :<br>REV : |
| SCHEDULE OF TECHNICAL DATA                  |                             |                 |
| 1. SERVICE                                  | TRAVERSING                  |                 |
| 2. MANUFACTURE                              | LK HOIST CO. LTD            |                 |
| 3. MOTOR MODEL NO                           | 0.4 - 6 - 38                |                 |
| 4. RATED POWER                              | 0.4 KW × 6 P                |                 |
| 5. RATED VOLTAGE AND FREQUENCY              | 380 V                       | 60HZ            |
| 6. ROTOR TYPE                               | SQUIRREL CAGE ROTOR TYPE    |                 |
| 7. RATING                                   | 15 MIN                      |                 |
| 8. LOCATION                                 | OUTDOOR                     |                 |
| 9. INSULATION CLASS                         | B                           |                 |
| 10. DESIGN TEMPERATURE RISE (BY RESISTANCE) | 100℃                        |                 |
| 11. FULL LOAD SPEED                         | 1140 RPM                    |                 |
| 12. FULL LOAD CURRENT                       | 1.85 A                      |                 |
| 13. STARTING CURRENT AT RATED VOLTAGE       | 10.5 A                      |                 |
| 14. MINIMUM STARTING VOLTAGE                | 342 V                       |                 |
| 15. EFFICIENCY AT 100% RATED LOAD           | 65 %                        |                 |
| 16. POWER FACTOR AT 100% RATED LOAD         | 63 %                        |                 |
| 17. STARTING TORQUE                         | 249 %                       |                 |
| 18. TYPE OF ENCLOSURE                       | 전폐형                         |                 |
| 19. TYPE OF BEARING                         | PL : 6008DD OPL : 6207ZZ    |                 |
| 20. MOUNTING                                | VERTICAL                    |                 |
| 21. MAXIMUM AMBIENT TEMPERATURE             | 40℃                         |                 |
| 22. BEARING LUBRICATION                     | GREASE                      |                 |
| 23. STARTING METHOD                         | FULL VOLTAGE                |                 |

|                                             |                             |                 |
|---------------------------------------------|-----------------------------|-----------------|
| SPECIFICATION FOR<br>ELECTRIC MOTORS        | INTERNAL IDENTIFICATION NO. | PAGE :<br>REV : |
| SCHEDULE OF TECHNICAL DATA                  |                             |                 |
| 1. SERVICE                                  | TRAVERSING                  |                 |
| 2. MANUFACTURE                              | LK HOIST CO. LTD            |                 |
| 3. MOTOR MODEL NO                           | 0.75/0.25 - 4/12 - 38       |                 |
| 4. RATED POWER                              | 0.75/0.25 KW × 4/12 P       |                 |
| 5. RATED VOLTAGE AND FREQUENCY              | 380 V                       | 60HZ            |
| 6. MOTOR TYPE                               | SQUIRREL CAGE ROTOR TYPE    |                 |
| 7. RATING                                   | 15 MIN                      |                 |
| 8. LOCATION                                 | OUTDOOR                     |                 |
| 9. INSULATION CLASS                         | B                           |                 |
| 10. DESIGN TEMPERATURE RISE (BY RESISTANCE) | 100℃                        |                 |
| 11. FULL LOAD SPEED                         | 1670 / 550 RPM              |                 |
| 12. FULL LOAD CURRENT                       | 2.77 / 1.74 A               |                 |
| 13. STARTING CURRENT AT RATED VOLTAGE       | 15.3 / 9.57 A               |                 |
| 14. MINIMUM STARTING VOLTAGE                | 342 V                       |                 |
| 15. EFFICIENCY AT 100% RATED LOAD           | 65 / 48 %                   |                 |
| 16. POWER FACTOR AT 100% RATED LOAD         | 63 / 46 %                   |                 |
| 17. STARTING TORQUE                         | 249/ 245 %                  |                 |
| 18. TYPE OF ENCLOSURE                       | 전폐형                         |                 |
| 19. TYPE OF BEARING                         | PL : 6008DD OPL : 6207ZZ    |                 |
| 20. MOUNTING                                | VERTICAL                    |                 |
| 21. MAXIMUM AMBIENT TEMPURE                 | 40℃                         |                 |
| 22. BEARING LUBRICATION                     | GREASE                      |                 |
| 23. STARTING METHOD                         | FULL VOLTAGE                |                 |