

FEC CHAIN

CORPORATION

TEL:+81-53-425-4116 , 2162

337 KANAORI-CHO , HAMAMATSU CITY,

SHIZUOKA PRE.,435-0026 JAPAN

FAX:+81-53-425-5122

TEST CERTIFICATE

Distributor:	code #: 1080	distributor's name: ASAO & CO., LTD
Customer:		customer's name: LK HOIST CO.,LTD
Article name: (Application)	Load chain for electric chain hoist	
Spec. standard	☐ DIN EN 818-7:2002 , ☐ JIS B 8812:1999 ☐ ISO 3077 , ☒ FEC	
Material spec.:	SAE15B24(Mn-B steel)	
Finish:	☒ temper-colored, ☐ zinc-plated, ☐ coated() ☐ zinc-phosphated, ☐ manganese-phosphated ☒ oiled, ☐ no-oiled	
Stamping:	☐ FEC standard, ☒ customer's request → LK, JAPAN , (Lot #), FEC9	
Product code#:	FCD11234	
description:	φ 11.2*P34	
quality type	G80/ type-DAT	

			Result
Dimention:			
Nominal diameter(dn)	[mm]	11.2 +0.3/-0.3	11.1~11.2
Internal width,min.:	[mm]	14.7	14.8~14.9
external width, max.:	[mm]	37.5	37.2~37.3
Nominal pitch 1 t	[mm]	34.0 +0.4/-0.2	34.3~34.4
5 t	[mm]	-	-
11 t	[mm]	374.0 +1.3/-0.4	374.1~375.2
Diameter at the weld(ds), max.:	[mm]	12.0	11.8~11.9

Mechanical properties:			
Working load limit(WLL), max.:	[kg]	3000	-
(drive mechanism g		-	-
Manufacturing proof force(MPF), min.:	[KN]	98	98
Stress at min. MPF		-	-
Guranteed breaking force(BF), min.:	[KN]	160	167~178
Stress at min. BF		-	-
Total ultimate elongation(A), min.:	[%]	10	12~15
Surface hardness/HV3, min.:	[—]	500	565~620
/HV5, min.:	[—]	-	-
Hardness /HRC, min.:	[—]	-	-
Case depth,min.:	[mm]	0.22	0.24~0.30
Bend deflection(f),min.:	[mm]	no visible defect	OK
Fatigue resistance, min.:	[cycle]	2*10 ⁶	OK

Packing:		
Weight per meter:	[kg/m]	2.65
Length 1	[meter]	100m-30/pcs
2	[meter]	
Packing	-	Steel barrel

I hereby certify above all is true.

M. Ota

MASAYUKI OTA

Quality Assurance Dept.,

Chief Inspector

issued date: December 26,2009

[Note]