

## LOAD LIMITER SETTING 勸告置

POWER SOURCE AC 3Φ 50Hz

POWER SOURCE (V)	HOIST 規格 (TON)	MOTOR 容量 Kw x P	MOTOR CURRENT ( A )		LOAD LIMITER SETTING置			CURRENT TRANSFORMER SPEC				
			100%負荷時	110%負荷時	負荷電流 %	作動時間 (SEC)	SHOCK時間 (SEC)	MODEL	貫通回數 (TURN)	連結 1次	1次測電流 (A)	2次測電流 (A)
220V	1S	1.8 x 4	8.5A	8.4A	110	1	1	CT-1	1	K-1	50	5
		1.2 x 6	8.9A	9A								
380V	1S	1.8 x 4	4.9A	4.6A	110	1	1	CT-1	1	K-1	50	5
		1.2 x 6	5.2A	5.4A								
440V	1S	1.8 x 4	4.3A	4.2A	110	1	1	CT-1	1	K-1	50	5
		1.2 x 6	4.5A	4.6A								
460V	1S	1.8 x 4	4.1A	4.0A	110	1	1	CT-1	1	K-1	50	5
		1.2 x 6	4.3A	4.4A								
480V	1S	1.8 x 4	4.0A	3.8A	110	1	1	CT-1	1	K-1	50	5
		1.2 x 6	4.1A	4.2								

☞ 제품의 성능향상을 위하여 권고치가 다소 변동이 될 수 있음.