

LOAD LIMITER SETTING 勸告置 (DB-TYPE)

POWER SOURCE AC 3Ø 60Hz

| POWER<br>SOURCE<br>(V) | HOIST<br>規 格<br>(TON) | MOTOR<br>容 量<br>(Kw×P) | MOTOR CURRENT(A) |             |             | LOAD LIMITER SETTING |               |                      | CURRENT TRANSFORMER SPEC |      |      |              |              |
|------------------------|-----------------------|------------------------|------------------|-------------|-------------|----------------------|---------------|----------------------|--------------------------|------|------|--------------|--------------|
|                        |                       |                        | 定 格              | 100%<br>負荷時 | 110%<br>負荷時 | 負荷電流<br>(%)          | 作動時間<br>(SEC) | SHOCK<br>時間<br>(SEC) | MODEL                    | 貫通回數 | 連結端子 | 1次測電流<br>(A) | 2次測電流<br>(A) |
| 220V                   | 1.5S<br>(1.5TON)      | 4.4/2.2Kw<br>×2/6P     | 20/10A           | 13.5/9.3A   | 16.2/9.8A   | 110                  | 1             | 1                    | CT-1                     | 1    | K-1  | 50           | 5            |
| 380V                   | 2S<br>(2TON)          | 4.4/2.2Kw<br>×2/6P     | 13/6.5A          | 7.9/5.4A    | 9.4/5.7A    | 110                  | 1             | 1                    | CT-1                     | 1    | K-1  | 50           | 5            |
| 440V                   | 2.8W<br>(2.8TON)      | 4.4/2.2Kw<br>×2/6P     | 11.2/5.6A        | 6.8/4.7A    | 8.1/4.9A    | 110                  | 1             | 1                    | CT-1                     | 1    | K-1  | 50           | 5            |
| 460V                   | 3W<br>(3TON)          | 4.4/2.2Kw<br>×2/6P     | 11/5.3A          | 6.5/4.5A    | 7.7/4.7A    | 110                  | 1             | 1                    | CT-1                     | 1    | K-1  | 50           | 5            |
| 480V                   | 5W<br>(5TON)          | 4.4/2.2Kw<br>×2/6P     | 10.5/5.1A        | 6.2/4.3A    | 7.3/4.5A    | 110                  | 1             | 1                    | CT-1                     | 1    | K-1  | 50           | 5            |

☞ 製品の性能 向上を 위하여 권고치가 다소 변동될 수 있음