

FEC CHAIN

CORPORATION

TEL:+81-53-425-4116 , 2162

337 KANAORI-CHO ,MINAMI-KU, HAMAMATSU CITY,

SHIZUOKA PREF.,435-0026 JAPAN

FAX:+81-53-425-5122

TEST CERTIFICATE

Distributor: code #: 1080 distributor's name: ASAO & CO., LTD
 Customer: customer's name: LK HOIST CO.,LTD

Article name: Load chain for electric chain hoist
 (Application)

Spec. standard DIN EN 818-7:2002 , JIS B 8812:1999
 ISO 3077 , FEC

Material spec.: SAE15B24(Mn-B steel)

Finish: temper-colored, zinc-plated, coated()
 zinc-phosphated, manganese-phosphated
 oiled, no-oiled

Stamping: FEC standard, customer's request
 LKA, JAPAN , FEC7
 → (Lot. 13,2A,2C,41,42,43,44,4S,4T,4U,4X,4Y)

Product code#: FCD07121
 description: φ 7.1*P21
 quality type G80/ type-DAT

			Result
Dimention:			
Nominal diameter(dn)	[mm]	7.1 +0.0/-0.3	7.0~7.1
Internal width,min.:	[mm]	8.4	8.7~9.3
external width, max.:	[mm]	23.2	22.7~23.1
Nominal pitch 1 t	[mm]	21.0 +0.4/-0.0	21.0~21.2
5 t	[mm]	-	-
11 t	[mm]	231.0 +1.1/-0.0	231.2~232.0
Diameter at the weld(ds), max.:	[mm]	7.6	7.3~7.6

Mechanical properties:			
Working load limit(WLL), max.:	[kg]	1200	-
(drive mechanism g		-	-
Manufacturing proof force(MPF), min.:	[KN]	40	40
Stress at min. MPF		-	-
Guranteed breaking force(BF), min.:	[KN]	63	78.0~88.0
Stress at min. BF		-	-
Total ultimate elongation(A), min.:	[%]	10	12~14
Surface hardness/HV3, min.:	[-]	500	529~593
/HV5, min.:	[-]	-	-
Hardness /HRC, min.:	[-]	-	-
Case depth,min.:	[mm]	0.14	0.16~0.22
Bend deflection(f),min.:	[mm]	no visible defect	OK
Fatigue resistance, min.:	[cycle]	2*10 ⁶	OK

Packing:		
Weight per meter:	[kg/m]	1.1
Length 1	[meter]	200m-51/pcs
2	[meter]	
Packing	-	Steel barrel

I hereby certify above all is true.

M. Miwa

MASAKI MIWA

Quality Assurance Dept.,

Chief Inspector

issued date: May 10,2017

[Note]

