

## LOAD LIMITER SETTING 勸告置 (DB-TYPE)

POWER SOURCE AC 3Ø 60Hz

POWER SOURCE (V)	HOIST 規格 (TON)	MOTOR 容量 (Kw×P)	MOTOR CURRENT(A)			LOAD LIMITER SETTING			CURRENT TRANSFORMER SPEC				
			定 格	100% 負荷時	110% 負荷時	負荷電流 (%)	作動時間 (SEC)	SHOCK 時間 (SEC)	MODEL	貫通回數	連結端子	1次測電流 (A)	2次測電流 (A)
220V	0.5S (0.5TON) 1S (1TON) 1.9W (1.9TON) 2W (2TON)	1.8/0.7Kw ×2/6P	12.6/4.7A	12/4.5A	13.2/4.9A	110	1	1	CT-1	1	K-1	50	5
380V		1.8/0.7Kw ×2/6P	7.1/2.8A	6.8/2.7A	7.4/2.9A	110	1	1	CT-1	1	K-1	50	5
440V		1.8/0.7Kw ×2/6P	6.3/2.4A	6.0/2.3A	6.6/2.5A	110	1	1	CT-1	1	K-1	50	5
460V		1.8/0.7Kw ×2/6P	5.9/2.1A	5.7/2.0A	6.2/2.2A	110	1	1	CT-1	1	K-1	50	5
480V		1.8/0.7Kw ×2/6P	5.1/1.8A	4.9/1.7A	5.3/1.9A	110	1	1	CT-1	1	K-1	50	5

☞ 제품의 성능 향상을 위하여 권고치가 다소 변동될 수 있음