

LOAD LIMITER SETTING 勸告置 (DB-TYPE)

POWER SOURCE AC 3Ø 60Hz

POWER SOURCE (V)	HOIST 規 格 (TON)	MOTOR 容 量 (Kw×P)	MOTOR CURRENT(A)			LOAD LIMITER SETTING			CURRENT TRANSFORMER SPEC				
			定 格	100% 負荷時	110% 負荷時	負荷電流 (%)	作動時間 (SEC)	SHOCK 時間 (SEC)	MODEL	貫通回數	連結端子	1次測電流 (A)	2次測電流 (A)
220V	1.5S (1.5TON)	4.4/2.2Kw ×2/6P	20/10A	13.5/9.3A	16.2/9.8A	110	1	1	CT-1	1	K-1	50	5
380V	2S (2TON)	4.4/2.2Kw ×2/6P	13/6.5A	7.9/5.4A	9.4/5.7A	110	1	1	CT-1	1	K-1	50	5
440V	2.8W (2.8TON)	4.4/2.2Kw ×2/6P	11.2/5.6A	6.8/4.7A	8.1/4.9A	110	1	1	CT-1	1	K-1	50	5
460V	3W (3TON)	4.4/2.2Kw ×2/6P	11/5.3A	6.5/4.5A	7.7/4.7A	110	1	1	CT-1	1	K-1	50	5
480V	5W (5TON)	4.4/2.2Kw ×2/6P	10.5/5.1A	6.2/4.3A	7.3/4.5A	110	1	1	CT-1	1	K-1	50	5

☞ 제품의 성능 향상을 위하여 권고치가 다소 변동될 수 있음